



NASA SBIR 2008 Phase I Solicitation

S5.02 Sample Collection, Processing, and Handling

Lead Center: JPL

Participating Center(s): ARC, GSFC, JSC

Robust systems for sample acquisition, handling and processing are critical to the next generation of robotic explorers for investigation of planetary bodies (http://books.nap.edu/openbook.php?record_id=10432&page=R1). Limited spacecraft resources (power, volume, mass, computational capabilities, and telemetry bandwidth) demand innovative, integrated sampling systems that can survive and operate in challenging environments (extremes in temperature, pressure, gravity, vibration and thermal cycling). Relevant systems could be integrated on multiple platforms, however of primary interest are samplers that could be mounted on a mobile platform, such as a rover. For reference, current Mars-relevant rovers range in mass from 200 to 800 kg.

Sample Acquisition

Research should be conducted to develop compact, low-power, lightweight subsurface sampling systems that can obtain 1 cm diameter cores of consolidated material (e.g., rock, icy regolith) up to 10 cm below the surface. Systems should be capable of autonomously acquiring and ejecting samples reliably. Other sample types of interest are unconsolidated regolith, dust, and atmospheric gas.

Sample Manipulation (core management, sub-sampling/sorting)

Sample manipulation technologies are needed to enable handling and transfer of structured and unstructured samples from a sampling device to instruments and sample processing systems. Core and regolith samples may be variable in size and composition, so a sample manipulation system needs to be flexible enough to handle the sample variability. Core samples will be on the order of 1 cm diameter and up to 10 cm long. Soil and rock fragment samples will be of similar volumes.

System Robustness and Reliability

Consideration should be given to potential failure scenarios for integrated systems. For example, recovery and mitigation techniques for platform slip and borehole misalignment should be addressed. Significant attention should be given to the sensing and automation required for real-time control, fault diagnosis and recovery. In the case of rover-mounted subsurface sampling systems, the ability to release under load will be critical to mitigate risk of losing mobility if unexpected subsurface conditions are encountered.

Sample Integrity (encapsulation and contamination)

For a sample return mission, it is critical to find solutions for maintaining physical integrity of the sample during the surface mission (rover driving loads, diurnal temperature fluctuations) as well as the return to Earth (cruise, atmospheric entry and impact). Technologies are needed for characterizing state of sample in situ and

physical integrity (e.g., cracked, crushed), sample volume, mass or temperature, as well as retention of volatiles in solid (core, regolith) samples, and retention of atmospheric gas samples.

Also of particular need are means of acquiring subsurface rock and regolith samples with minimum contamination. This contamination may include contaminants in the sampling tool itself, material from one location contaminating samples collected at another location (sample cross-contamination), or Earth-source microorganisms brought to the Martian surface prior to drilling ('clean' sampling from a 'dirty' surface). Consideration should be given to use of materials and processes compatible with 110-125°C dry heat sterilization. In situ sterilization may be explored, as well as innovative mechanical or system solutions; e.g., single-use sample sleeves; or fully-integrated sample acquisition and encapsulation systems.

For a sample return mission, sample transfer of a payload into a Planetary Ascent Vehicle (PAV)

- Automated payload transfer mechanisms;
- Orbiting Sample (OS) sealing techniques.

Proposals should show an understanding of one or more relevant science needs, and present a feasible plan to fully develop a technology and infuse it into a NASA program.