



## NASA SBIR 2008 Phase I Solicitation

### S2.03 Precision Deployable Optical Structures and Metrology

Lead Center: JPL

Participating Center(s): GSFC, LaRC

Planned future NASA Missions in astrophysics, such as the Single Aperture Far-IR (SAFIR) telescope, James Webb Space Telescope (JWST, <http://www.jwst.nasa.gov/>), Terrestrial Planet Finder (TPF, [http://planetquest.jpl.nasa.gov/TPF/tpf\\_index.cfm](http://planetquest.jpl.nasa.gov/TPF/tpf_index.cfm)) missions: Coronagraph, External Occulter and Interferometer, ATLAST, Life Finder, and Submillimeter Probe of the Evolution of Cosmic Structure (SPECs), and the UV Optical Imager (UVOIR) require 10 - 30 m class cost effective telescope observatories that are diffraction limited at wavelengths from the visible to the far IR, and operate at temperatures from 4 - 300 K. The desired areal density is 1 - 10 kg/m<sup>2</sup>. Static and dynamic wavefront error tolerances to thermal and dynamic perturbations may be achieved through passive means (e.g., via a high stiffness system, passive thermal control, jitter isolation or damping) or through active opto-mechanical control. Large deployable multi-layer structures in support of sunshades for passive thermal control and 20m to 50m class planet finding external occulter are also relevant technologies. Potential architecture implementations must package into an existing launch volume, deploy and be self-aligning to the micron level. The target space environment is expected to be L2.

This topic solicits proposals to develop enabling, cost effective component and subsystem technology for these telescopes. Research areas of particular interest include precision deployable structures and metrology (i.e., innovative active or passive deployable primary or secondary support structures); innovative concepts for packaging fully integrated (i.e., including power distribution, sensing, and control components); distributed and localized actuation systems; deployment packaging and mechanisms; active opto-mechanical control distributed on or within the structure; actuator systems for alignment of reflector panels (order of cm stroke actuators, lightweight, nanometer stability); innovative architectures, materials, packaging and deployment of large sunshields and external occulter; mechanical, inflatable, or other deployable technologies; new thermally-stable materials (CTE < 1ppm) for deployables; innovative ground testing and verification methodologies; and new approaches for achieving packagable depth in primary mirror support structures.

Also of interest are innovative metrology systems for direct measurement of the optical elements or their supporting structure; requirements for micron level absolute and subnanometer relative metrology for multiple locations on the primary mirror; measurement of the metering truss; and innovative systems which minimize complexity, mass, power and cost. The goal for this effort is to mature technologies that can be used to fabricate 20 m class or greater, lightweight, ambient or cryogenic flight-qualified observatory systems. Proposals to fabricate demonstration components and subsystems with direct scalability to flight systems through validated models will be given preference. The target launch volume and expected disturbances, along with the estimate of system performance, should be included in the discussion. A successful proposal shows a path toward a Phase 2 delivery of demonstration hardware scalable to 3 m for characterization.

---

Proposals should show an understanding of one or more relevant science needs, and present a feasible plan to fully develop a technology and infuse it into a NASA program.Â