



## NASA SBIR 2018 Phase I Solicitation

### S4.04 Extreme Environments Technology

Lead Center: JPL

Participating Center(s): ARC, GRC, GSFC, LaRC, MSFC

Technology Area: TA4 Robotics, Telerobotics and Autonomous Systems

NASA is interested in expanding its ability to explore the deep atmosphere and surface of giant planets, asteroids, and comets through the use of long-lived (days or weeks) balloons and landers. Survivability in extreme high-temperatures and high-pressures is also required for deep atmospheric probes to planets. Proposals are sought for technologies that are suitable for remote sensing applications at cryogenic temperatures, and in-situ atmospheric and surface explorations in the high-temperature high-pressure environment at the Venusian surface (485° C, 93 atmospheres), or in low-temperature environments such as Titan (-180° C), Europa (-220° C), Ganymede (-200° C), Mars, the Moon, asteroids, comets and other small bodies. Also, Europa-Jupiter missions may have a mission life of 10 years and the radiation environment is estimated at 2.9 Mega-rad total ionizing dose (TID) behind 0.1-inch-thick aluminum. Proposals are sought for technologies that enable NASA's long duration missions to extreme wide-temperature and cosmic radiation environments. High reliability, ease of maintenance, low volume, low mass, and low out-gassing characteristics are highly desirable. Special interest lies in development of following technologies that are suitable for the environments discussed above:

- Wide temperature range precision mechanisms i.e., beam steering, scanner, linear and tilting multi-axis mechanisms.
- Radiation-tolerant/radiation hardened low-power low-noise mixed-signal mechanism control electronics for precision actuators and sensors.
- Wide temperature range feedback sensors with sub-arc-second/nanometer precision.
- Long life, long stroke, low power, and high torque/force actuators with sub-arc-second/nanometer precision.
- Long life Bearings/tribological surfaces/lubricants.
- High temperature energy storage systems.
- High-temperature actuators and gear boxes for robotic arms and other mechanisms.
- Low-power and wide-operating-temperature radiation-tolerant /radiation hardened RF electronics.
- Radiation-tolerant/radiation-hardened, low-power/ultra-low-power, wide-operating-temperature, low-noise, mixed-signal electronics for space-borne system such as guidance and navigation avionics and instruments.
- Radiation-tolerant/radiation-hardened power electronics.
- Radiation-tolerant/ radiation-hardened electronic packaging (including, shielding, passives, connectors, wiring harness and materials used in advanced electronics assembly).

Research should be conducted to demonstrate technical feasibility during Phase I and show a path toward a Phase II hardware demonstration, and when possible, deliver a demonstration unit for functional and environmental testing at the completion of the Phase II contract.

---

Please see subtopic Z8.03 for related topics of potential interest.